

# RELEASE NOTES

Document revision: A

February 15, 2024

The information contained herein is the property of Mecademic Inc. and shall not be reproduced in whole or in part without prior written approval of Mecademic Inc. The information herein is subject to change without notice and should not be construed as a commitment by Mecademic Inc. This manual will be periodically reviewed and revised.

Make sure that the firmware of your robot is the one indicated on the cover of this manual, or else consult the manual corresponding to your robot's firmware. Ideally, always use the latest robot firmware.

If you have any technical questions, please use the technical support form on our web site (<https://support.mecademic.com/>).

Mecademic Inc. assumes no responsibility for any errors or omissions in this document.

Copyright © 2024 by Mecademic Inc.

# Contents

Version 10.1.0 . . . . .	3
Version 10.0.4 . . . . .	4
Version 10.0.3 . . . . .	5

## Version 10.1.0

### Features

- (ROBOT-2239) New robot API command 'SetPStop2Cfg'/'GetPStop2Cfg' for PStop2 configuration.
- (ROBOT-2451) Support for collision prevention and work zone features:
  - New robot API command 'SetCollisionCfg'/'GetCollisionCfg' for collision prevention configuration.
  - New robot API command 'SetWorkZoneCfg'/'GetWorkZoneCfg' for work zone configuration.
  - New robot API command 'SetWorkZoneLimits'/'GetWorkZoneLimits' for defining work zone bounding box.
  - New robot API command 'SetToolSphere'/'GetToolSphere' for defining tool sphere model.
  - New field 'CollisionStatus' in 'RobotStatus' cyclic protocol data.
  - New field 'WorkZoneStatus' in 'RobotStatus' cyclic protocol data.
  - Visual representations for reporting feature events in MecaPortal.
- (ROBOT-2825) Support for Mcs500 safety behaviors:
  - Support for Operation modes and key switch selector.
  - Support for speed limitation to 250 mm/s in Manual mode.
  - Support for safety standstill monitoring.
  - Conditional logic for 3-position enabling device.
  - New structure 'SafetyStatus' and fields related to safety signals in cyclic protocol data.

### Fixed

- (ROBOT-2784) Gripper instabilities while holding part.
- (ROBOT-2833) Issues related to robot running large offline programs.
- (ROBOT-2837) SetTimeScaling not working on Meca500 on EtherCAT.
- (ROBOT-2859) Mcs500 cyclic data for joint limits of joint 4 reports no data.
- (ROBOT-2891) Brake Release not allowed if Pstop2 is on.

- (ROBOT-2898) Some state change events were sent on Control port instead of Monitoring port (safety stops, torque limit status).
- (ROBOT-2907) Robot activation may fail if robot is moving when trying to activate (tool weight causing movement due to gravity for example). The robot may now post-pone activation by few seconds, waiting until it stopped moving.

IMPORTANT: The following behavior changes have been implemented in version 10.1. If you are upgrading from a previous version (ex. 10.0 or 9.3), this section will be of particular importance:

- (ROBOT-2784) In fixing the instabilities issues, the overall speed of the gripper has been reduced. In cases where the legacy max gripper velocity is required, 'SetGripperVel' can accept up to 200%, but will only go to those excess speeds when the gripper force is at 100%.
- (ROBOT-2939) The method for resuming robot motion using cyclic protocols (EtherCAT, EtherNet/IP or Profinet) has changed. In addition to clearing 'Pause Motion' and 'Clear Motion' bits, resuming motion now also requires to set the 'Resume Motion' bit. This 'Resume Motion' bit is replacing the previous 'Reset PStop2' bit in the cyclic data, now that the 'Resume Motion' command has been generalized. In fact, the 'Resume Motion' command is now used not only to resume paused motion, but also to recover from safety stop signals (such as PStop2, enabling device released or connection dropped) or recover from collision or work zone event. Note that motion is resumed only upon rising edge of the 'Resume Motion' bit so if, for any reason, the robot is refusing to resume motion (PStop2 signal is still present for example) the application will have to clear the 'Resume Motion' bit and set it again later.
- The alpha feature denoted *WorkspaceLimits* has been deprecated. Commands from *WorkspaceLimits* (SetWorkspaceLimitsCfg, GetWorkspaceLimitsCfg, SetWorkspaceLimits, GetWorkspaceLimits) have been changed for new commands. Please refer to the Programming Manual for equivalent commands in the work zone and collision prevention features.

## Version 10.0.4

### Fixed

- (ROBOT-2783) Meca500 joint offset after activation without homing.
- (ROBOT-2811) Mcs500 can't move to joint 3 limits with MoveLinVel when TRF has Z offset.
- (ROBOT-2815) MecaPortal visual scaling enhancements.

- (ROBOT-2823) Missing response to SetTimeScaling.
- (ROBOT-2832) Some MSIPS R1 power supplies (for Mcs500 robots) generate a fatal error after a long press on the reset button.
- (ROBOT-2833) Robot becomes unresponsive when starting too many large offline programs.
- (ROBOT-2834) Profinet and EtherNet/IP cyclic data is delayed when starting a large program.

## Version 10.0.3

### Features

- (ROBOT-892) Support for new Mcs500 Scara robot.
- (ROBOT-1598) Support for robot calibration (with full DH parameters and more).
- (ROBOT-2552) Support for time scaling (real-time robot execution speed control without affecting the followed trajectory).
- (ROBOT-2680) Various minor MecaPortal enhancements.
- (ROBOT-2682) Support for new Mvk01 vacuum and digital IO module for Mcs500 robot. New API calls allow to control vacuum and digital IOs.
- (ROBOT-2700) New MoveJump command for Mcs500 robot.
- (ROBOT-2746) Pause motion now follows planned path (no more ignores blending).

IMPORTANT: The following behavior changes have been implemented in version 10.0. If you are upgrading from a previous version (ex. 9.3), this section will be of particular importance:

- (ROBOT-1687) EtherCAT COE is not supported on Mcs500 robots (though cyclic PDO communication protocol remains the same on both Mcs500 and Meca500 robots).
- (ROBOT-2641) Behavior of the Delay command has been changed on Mcs500 robots to be more consistent. On Meca500 robots, the Delay command is being blended with previous/next commands when executed in joint space but not in Cartesian space. On Mcs500 robots, the Delay command is now always causing the robot to come to a complete stop before the requested delay duration starts to be applied.
- (ROBOT-2746) Robot behavior during PauseMotion and ClearMotion have slightly changed:
  - Deceleration period has been uniformized to 100ms in both Joint and Cartesian modes (in Joint mode it used to depend on joint acceleration and could thus take very long to stop moving).
  - Deceleration is now made along the planned path, including blending (it used to

ignore blending and stop like if blending was always set to 0 percent).